

qineo

QINEO STEP



QINEO STEP – nearly indestructible

MIG/MAG Pulsed arc welding power sources with integrated wire drive unit

CLOOS

Weld your way.

qineo

QINEO STEP C

350 A

60% duty cycle

400 A

60% duty cycle

600 A

60% duty cycle



QINEO STEP – nearly indestructible

Simple, practical, reliable. These are the characteristics of the QINEO STEP step-switch MIG/MAG welding power source. Each detail is targeted for manual industrial welding. With capacity modules of 350 A to 600 A weld current and an intuitive operation, the QINEO STEP can be exactly configured to any requirement. The best choice for the hard working life of a welding machine.

- **Absolutely reliable:** Due to robust modular design and proven welding characteristics
- **Universally applicable:** Five capacity classes for every requirement of manual welding
- **Best quality:** Optimum ignition and welding characteristics
- **Easy operation:** Intuitive user guidance, synergy mode as standard



Operating module Step

- **Intuitive adjustment:** Clear operating module for maximum user-friendliness
- **Synergy mode:** Quick parameter finding due to a number of characteristic curves

QINEO STEP	QINEO STEP C 350	QINEO STEP C 450	QINEO STEP C 600
Welding current	40 A - 350 A	40 A - 450 A	40 A - 600 A
Welding current at 60 % duty cycle	350 A / 31.5 V	450 A / 36.5 V	600 A / 44 V
Welding current at 100 % duty cycle	270 A / 27.5 V	350 A / 31.5 V	465 A / 37.5 V
Open circuit voltage	16 V - 40 V	19 V - 46 V	17 V - 54 V
Mains voltage	400 V / 50 Hz / 3 phases	400 V / 50 Hz / 3 phases	400 V / 50 Hz / 3 phases
Special voltages	Optionally	Optionally	Optionally
Steps	2 x 10	3 x 10	4 x 10
Connection cable	4 x 4 mm ²	4 x 6 mm ²	4 x 10 mm ²
Mains protection	25 A	32 A	50 A
Type of protection	IP 23	IP 23	IP 23
Insulating class	F	F	F
Type of cooling	F	F	F
Dimension L/W/H (without wire drive)	1226 x 630 x 741 mm	1226 x 630 x 741 mm	1226 x 630 x 741 mm
Weight (without wire drive)	189 kg	226 kg	280 kg
Maximum track width	approx. 552 mm	approx. 552 mm	approx. 552 mm
Operating modes	2 cycles, 4 cycles, External Start		

All over the world!



Carl Cloos Schweisstechnik GmbH
Main office: Carl-Cloos-Strasse 1
Central warehouse: Carl-Cloos-Strasse 6
35708 Haiger
GERMANY

Telephone +49 (0)2773 85-0
Telefax +49 (0)2773 85-275
E-Mail info@cloos.de



Arcent (Singapore) Pte Ltd

2, Yishun Industrial Street 1
Northpoint Bizhub #07-11
Singapore 768159
Tel: +65 6356 6997
Fax: +65 6356 4854

sales@arcentwelding.com
www.arcentwelding.com

CLOOS

Weld your way.