



HAZARD PROTECTION

Parweld's range of welding blankets & curtains protect the user from accidents caused by welding sparks. All Parweld welding blankets conform to BS EN 1869:1997

DEFINITIONS

BS EN ISO 1869:1997

THE PRODUCT MUST:

- Protect workers whilst having the added benefit of shielding flammable materials, machinery, vehicles & plant & equipment from molten metal globules, spatter, etc. Welding blankets are reusable dependent upon the application.
- Parweld's welding curtains can be used to isolate an area offering protection to workers working outside of the welding area from welding sparks, UV/IR light welding spatter by creating a moveable welding bay.
- Parweld's safety apparel offers the users protection against the hazards in the workplace.

ORANGE PVC WELDING CURTAIN



STOCK CODE

P3646O - Size 1.2m x 1.8m (4ft x 6ft)

P3666O - Size 1.8m x 1.8m (6ft x 6ft)

P3886O - Size 2.4m x 1.8m (8ft x 6ft)

P3610 - Curtain Rings

FEATURES

- Low visibility dark green PVC welding curtain for MIG and TIG welding
 - Supplied with eyelets on 4 sides
- UV Stabilised / PVC

STANDARDS

- BS EN ISO 25980:2014

STEEL FRAME



STOCK CODE

P3666FR - Size 1.8m x 1.8m (6ft x 6ft)

P3886FR - Size 2.4m x 1.8m (8ft x 6ft)

FR-EXT - Steel Frame Extension 0.6m (2ft)

FEATURES

- Low visibility dark green canvas welding curtain for MIG and TIG welding
- Supplied with eyelets on 4 sides

GREEN PVC WELDING CURTAIN



STOCK CODE

P3646G - Size 1.2m x 1.8m (4ft x 6ft)

P3666G - Size 1.8m x 1.8m (6ft x 6ft)

P3886G - Size 2.4m x 1.8m (8ft x 6ft)

P3610 Curtain Rings

FEATURES

- Low visibility dark green PVC welding curtain for MIG and TIG welding
- Supplied with eyelets on 4 sides

STANDARDS

- BS EN ISO 25980:2014

UV Stabilised / PVC

CANVAS WELDING CURTAIN



STOCK CODE

P3646CG - Size 1.2m x 1.8m (4ft x 6ft)

P3666CG - Size 1.8m x 1.8m (6ft x 6ft)

P3886CG - Size 2.4m x 1.8m (8ft x 6ft)

P3610 Curtain Rings

FEATURES

- Low visibility dark green canvas welding curtain for MIG and TIG welding
- Supplied with eyelets on 4 sides

STANDARDS

- BS EN ISO 25980:2014

Green Canvas

WELDING BLANKET/ROLL

WOVEN GLASS FIBRE WITH THERMAL TREATMENT



600°C

STOCK CODE

P3630

50m x 1m

P3621

2000m x 1000m

P3822

2000m x 2000m

P3623

3000m x 2000m

FEATURES

STANDARDS

- BS EN 1869:1997

- Provides protection from sparks and weld spatter
- 880G/Sq m

1000°C

STOCK CODE

P3631

50m x 1m

P3624

2000m x 1000m

P3825

2000m x 2000m

FEATURES

- Provides protection from sparks and weld spatter
- 430G/Sq m