

ELITE 110165

PUNCH

Rating: 110 Tons
Max. Capacity: 1-3/8" Dia. in 3/4" A36
Stroke: 3"
Throat Depth: 17-3/4"
Open Height: 9-3/4"
Shut Height: 6-9/16"
Work Height: 37-1/2"

FLAT BAR SHEAR

Rating: 65 Tons
Max. Capacity: 3/8" x 24"
1/2" x 14"
1" x 4"

Max. Round: 1"
Max. Square: 1"
Work Height: 33-1/2"

ANGLE SHEAR

Max. Capacity: 5" x 5" x 1/4"
Work Height: 44"

COPER NOTCHER

Max. Capacity: 2-1/2" x 6" x 3/8"
Work Height: 35-5/8"

GENERAL SPECIFICATIONS

Standard Motor:	7.5 HP 3 Phase 208/240v 1765 RPM 21 AMP
Optional Motors:	7.5 HP 3 Phase 440/480v 1765 RPM 12 AMP
	7.5 HP 3 Phase 575v 1770 RPM 8 AMP
	7.5 HP 1 Phase 208/240v 1765 RPM 36 AMP
Hydraulic Pump:	10-1/2 GPM - 2 Stage
Valve Pressure:	3000 PSI
Reservoir:	17 Gallons
Cylinder (Punch Side):	7-1/2" Bore / 3" Ram
Cylinder (Shear Side):	6" Bore / 3-1/2" Ram

OPEN CAVITY

Width: 11-3/4"
Height: 9"
Work Height: 40-7/8"

DIMENSIONS

Height:	65-1/8"
Width:	91-9/16"
Depth:	44-7/8"
Shipping Weight:	8580 lb

True Dual Operation
Five Workstations and Two Independent Power Plants
Super-size Punch Throat Depth of 17-3/4"
Universal Open Tooling Cavity
ANSI B11.5-1988R(02) Compliant and ETL/UL Approved Controls

ELITE Integrated Features:

Hydraulic Hold-Down	Swing-Away Stripper Assembly
E-Stop / Lockout-Tagout	Roller Encoder Measuring System
Electric Stroke Control	Quick Change Punch Assembly
Hydraulic Accessory Pack	Premium Gauging Tables
Central Lubrication System	LED Lighting



Shown with optional Pipe Notcher



Arcent (Singapore) Pte Ltd
2, Yishun Industrial Street 1
Northpoint Bizhub #07-11
Singapore 768159
Tel: +65 6356 6997
Fax: +65 6356 4854
sales@arcentwelding.com
www.arcentwelding.com